



Fish Finder

MODEL NO. FFNT918-100W(Wireless mode + Transducer 100M)

CE/ROHS Approved

PRODUCT SPECIFICATION:

- 1) Display: high contrast FSTN LCD
4-level grayscale, 160V X 132H
- 2) Power output (RMS): 100 W
- 3) Power output (peak-to-peak): 800 W
- 4) Operating frequency: 200 kHz(transducer/ 125 kHz (wireless)
- 5) Sonar coverage(transducer mode): 45 degrees at 200 kHz
- 6) Sonar coverage(wireless): 90 degrees at 125 kHz
- 7) Depth Units: Meters/Feet
- 8) Depth capability:328 feet (transducer mode 200KHZ)
140 feet (wireless mode 125KHZ)
- 9) Wireless operating range: Up to 165 feet
- 10) Target separation: 2.5 inches
- 11) Fresh/Salt Water Environment
- 12) Temperature sensor: included in transducer
- 13) Operational Temperature: From -10C to 50C (14 Fto122 F)
- 14) Power input: 10 to 20 V DC / 8 AA alkaline battery
- 16) Transducer mounting: Suction cup mount, wireless
- 17) Unit mounting: Portable case
- 18) Clear fish icon, fish alarm
- 19) Memory: Built -in memory stores sonar setting when the unit is turned off
- 20) W-Sensor could shut down when it is out of the water
- 21) W-Sensor battery requirement: One replaceable CR-2032 lithium battery
- 22)Operational wireless Frequency: 433.93mHz



MASTER CARTON SIZE AND DIMENSION :

MASTER CARTON CUBE : 10 PCS

MASTER CARTON WEIGHT : 16.5 KGS

MASTER CARTON DIMENSION : 0.071 CBM

MASTER CARTON DIMENSION : 57X43X29CM

PRODUCT MEASUREMENTS :

ITEM PACKING : 1 PC/CN

ITEM WEIGHT : 1.55 KG/PC

INNER BOX DIMENSION : 20X11X27.8CM

INNER BOX DIMENSION : 0.006 CBM



MODEL NO. FFNT1108

CE/ROHS Approved

PRODUCT SPECIFICATION:

- 1) Display: TN/ANTI-UV LCD
- 2) Display size: 40Wx39H
- 3) Small round transducer with 7m cable,45-degree beam angle
- 4) Removable float
- 5) Back lighting: Green LED backlight
- 6) 4xAAA batteries, battery save mode, battery strength indicator
- 7) High/Low sensitivity setting
- 8) Depth Range Max/Min: 328Feet(100meters)/2Feet(0.7meters)
- 9) Operational Temperature: -4F to 158F(-20C-70C)
- 10) Fish depth scale, audible fish alarm
- 11) User selectable meter or feet readings
- 12) Waterproof design: level-4 (spray-water-proof)
- 13) Able to shoot through boat hull and clear ice
- 14)Bottom show:Show the bottom grass or rock
- 15)Can resist the interference from the grass when use in lake



MASTER CARTON SIZE AND DIMENSION :

MASTER CARTON CUBE : 20 PCS

MASTER CARTON WEIGHT : 12.8 KGS

MASTER CARTON DIMENSION : 0.059 CBM

MASTER CARTON DIMENSION : 64x26x36CM

PRODUCT MEASUREMENTS :

ITEM PACKING : 1 PC/CN

ITEM WEIGHT : 0.55 KGS/PC

ITEM DIMENSION : 25X16.8X5.8 CN

INNER BOX DIMENSION : 0.0024 CBM



MODEL NO. FFNT718

CE/ROHS Approved

PRODUCT SPECIFICATION:

- 1) Depth Range Max/Min: 131Feet(40meters)/2Feet(0.7meters)
- 2) Wireless sensor: 90-degree beam angle
- 3) Display: Big Adjustable High-contrast Dot matrix FSTN LCD 128Vx64H
- 4) Display size: 41Wx48H
- 5) Back lighting: On/off White LED
- 6) 125KHz sonar frequency
- 7) Temperature unit: Celsius/Fahrenheit
- 8) Wireless operational Range: 165Feets(50meters)
- 9) Power Requirement: 4-AAA alkaline batteries
- 10) Battery strength indicator
- 11) Levels sensitivity setting
- 12) Clear fish icon, fish alarm
- 13) Bottom contour: Show true changing of water bottom contour
- 14) User selectable meter or feet readings
- 15) Water Temperature Indicator
- 16) Waterproof design: Level-4 (spray-water-proof)
- 17) Memory: Built -in memory stores sonar setting when the unit is turned off
- 18) W-Sensor could shut down when it is out of the water
- 19) W-Sensor battery requirement:One replaceable CR-2032 lithium battery
- 20) Operational Temperature: -4F to 158F(-20C-70C)



MASTER CARTON SIZE AND DIMENSION :

MASTER CARTON QUANTITY : 20 PCS

MASTER CARTON WEIGHT : 7.5 KGS

MASTER CARTON DIMENSION : 0.033 CBM

MASTER CARTON DIMENSION : 52x20x32CM

PRODUCT MEASUREMENTS :

ITEM PACKING : 1 PC

ITEM WEIGHT : 0.35 KGS/PC

INNER BOX DIMENSION : 16X11X9.5 cm

INNER BOX DIMENSION : 0.0016 CBM